

TIJ ONLINE PRINTER

ADVANCE BATCH CODING MACHINE

MODEL NO. G-910



Intelligent



Comfortable



High Performance



Touch Screen



No Maintenance



Easy Operation



USB Disk Transfer



10 Inch Controller

Support 1/2 & 1 Inch Ink Cartridges



2cm Adjustable Printer Head



4 Printing Head

Website : www.gravityprintech.com
Email us : mail@gravityprintech.com

+91-181-415 6009
+91-181-415 0077
+91-98759-85173

Gravity Printech India Pvt. Ltd
SCO # 7-10, 3rd Floor, PPR Mall
Mithapur Rd, Urban Estate phase II
Jalandhar, Punjab 144003

TIJ ONLINE PRINTER

ADVANCE BATCH CODING MACHINE

MODEL NO. G-910



PRODUCT PARAMETERS

- Screen: 10 inch capacitive screen (1024*600px)
- QTY of print heads: 1-4
- Printhead cables: 1.5m or customs, max is 8m
- PC software format: MS excel, ms access, SQL2000, SQL2005, SQL2008
- Ink cartridge types: half inch and one inch, solvent based, water based, oil based
- Print height: use half inch cartridge: 12.7-50mm, use one inch 25.4-100mm Print speed: fix data: 120m/min (300*300dpi, grey level1)
- Resolution: 300dpi
- Grey level: -2 to 6, total 8 levels
- Throw distance: 2-5mm
- Image format: jpg/png/bmp/css/web
- Table format: xls/xlsx/csv/txt
- Variable data format: csv/txt/xls/xlsx
- variable data: 75m/min (3 kinds of variable datas: QR code center+time)
- External connection: power supply/print heads/encoder/sensor/alarm light/USB/RS232 LAN
- Print content: text/variable data/date & time/batch/counter/barcode/QR code/GS1/ logo/ Database/real-time data etc
- Font: can be added freely, support TTF/OTF/TTC format
- Codes: Code39/code128/UPCA/EAN8/EAN13/Data Matrix/EAN14/UPCE/INT25 ITF14/Code93/ PDF417/Grid/Matrix/Code11/Code39+/Code16k/Code49 Flattermarken/VIN/NVE-18/Micro PDF417/ Micro QR code/GS1 DataBar-14 GS1 DataBar-EXP/GS1 DataBar-Ltd/GS1 DataBar-Stack/GS1 DataBar-Stack Omni/GS1 DataBar-Exp-Stack/GS1 EAN128/GS1-DM/GS1-QRcode/
- Aztec Code, can be added according
- Date format: can be customs by yourself, Julian year/Julian day
- System of numeration: Binary system/Octal/decimalism/hexadecimal Protocol/Network port protocol Serial port protocol (RS232)
- Operation system: Android CPU: Quad-core processor 1.5GHz
- Storage capacity: 32G EMMC memory card, 12G capacity storage for user Ink management: Automatically calculates left ink, and how many prints can do. Which for estimating cost.
- User management: add different users and assign them with different operations Electrical supply: Input: AC100-240V,50/60Hz Output: 32V/3A (single head) or 32V/5A (2-4heads)
- Operation Temperature: 0-45°C (32-113°F)
- Humidity: 20-80%RH
- Specification subject to change without notice



EITHER HALF INCH AND 1 INCH CARTRIDGE CAN WORK ON A SAME PRINTER ONLY BY CHANGING THE PRINT HEAD PLATE



SUPPORT 1-4 HEADS, CAN BE STITCHED OR SEPERATELY, GOOD OR DIFFERENT APPLICATIONS



PRINT HEAD AND CONTROLLER ARE PRE CONNECTED TO REDUCE HUMAN INTERVENTION

Website : www.gravityprintech.com
Email us : mail@gravityprintech.com

+91-181-415 6009
+91-181-415 0077
+91-98759-85173

Gravity Printech India Pvt. Ltd
SCO # 7-10, 3rd Floor, PPR Mall
Mithapur Rd, Urban Estate phase II
Jalandhar, Punjab 144003